



TDS
SMOG DOCTOR VL C2/C3 5W30

Application:

SMOG DOCTOR VL C2/C3 5W30 Engine oil of unique quality produced in 100% from synthetic base oils. The oil meets the latest requirements of car manufacturers. The oil provides engine protection under all conditions, reducing fuel consumption and thanks to high stability allows extension of oil drain intervals. Suitable for petrol engines working in various conditions. It is recommended for use in engines equipped with DPF – diesel particulate filter and TWC – three-way catalyst. It helps to reduce environmental harmful compounds, minimizing fuel consumption, without lowering the engine's power. It is recommended for vehicles that meet the requirements of Euro 6 standard. Preferred for BMW, Mercedes – Benz and Volkswagen cars. Ready to be mixed with other branded motor oils of this kind.

Specifications and Standards:

viscosity grade SAE: 5W30

Quality class API: SN

Quality class ACEA: C2/C3

Recommended to: BMW Longlife 04, MB 229.51, MB 229.52, VW 502.00/505.00/505.01,
Renault RN 0700/0710, GM DEXOS 2

Typical physico-chemical attributes

SMOG DOCTOR VLC2/C3 5W30	Typical value
Kinematic Viscosity Index at 100 °C, mm ² /s	10.8
Viscosity Index	161
TBN (mg KOH/g)	8
HTHS(cP)@150°C	3,32
Pour Point, °C	-45
Flash Point, °C	234